

## Ponorná vrtací kladiva firmy Joytech

MODEL (SIZE)	JQ20 (2")	JQ35 (3.5")	JQ40 (4")	JQ50 (5")	JQ60 (6")	JQ80 (8")	JQ100 (10")	JQ120 (12")	JQ200 (20")
SHANK TYPE	MACH20	DHD3.5 XL3 MACH303 COP34	QL40 DHD340 SD4 MACH44	QL50 DHD350 SD5 MACH50	QL60 DHD360 SD6 XL6 MACH60	QL80 DHD380 SD8 MACH80	NUMA100 SD10	QL120 DHD112 SD12 NUMA120 NUMA125	QL200
HOLE DIA.	70~76mm (2-3/4"~3")	86~127mm (3-3/8"~5")	105~130mm (4-1/8"~5-1/8")	127~152mm (5" ~ 6")	150~216mm (5-7/8"~8-1/2")	200~254mm (7-1/2"~10")	254~311mm (10"~12-1/4")	300~445mm (11-7/8~17-1/2")	445mm~660mm (17-1/2"~26")
HAMMER O.D.	60mm (2.4")	80mm (3.1")	98mm (3.86")	115mm (4.5")	137.5mm (5.4")	180mm (7.09")	225mm (8.86")	274mm (10.79")	396mm (15.59")
CYLINDER BORE	45mm (1.77")	67mm (2.64")	82mm (3.23")	95mm (3.74")	114mm (4.65")	152mm (5.98")	174mm (6.85")	220mm (8.66")	311mm (12.24")
LENGTH	680mm (26.75")	863mm (34")	1030mm (40.51")	1,127.5mm (44.35")	1,266mm (49.8")	1,359mm (53.50")	1,489.5mm (58.64")	1,897mm (74.69")	1,951mm (76.81")
WEIGHT	13kg (28.7lb)	20kg (44lb)	37.6kg (82.9lb)	57.4 kg (126.4 lb)	92.2 kg (203.2 lb)	166.3 kg (366.7 lb)	325 kg (715 lb)	620 kg (1,364 lb)	1,542 kg (3,392 lb)
TOP SUB CONNECTION	50mm DIN 405 6TPI BOX	2-3/8" API REG PIN	2-3/8" API REG PIN	3-1/2" API REG PIN	3-1/2" API REG PIN	4-1/2" API REG PIN	6-5/8" API REG PIN	6-5/8" API REG PIN	8-5/8" API REG PIN
<b>AIR CONSUMPTION, CFM(M<sup>3</sup>/MIN)</b>									
100PSI(6.8BAR)	70(2)	140(4)	150(4.2)	180(5.1)	.	.	400(11.3)	750(21.2)	1,584(45.2)
150PSI(10.3BAR)	135(3.8)	230(6.5)	240(6.8)	280(7.9)	350(9.9)	450(12.7)	655(18.5)	1,125(31.9)	2,470(70.5)
200PSI(13.8BAR)	205(5.8)	330(9.3)	340(9.6)	400(11.3)	565(16)	530(15)	945(26.8)	1,675(47.4)	3,389(96.8)
250PSI(17.2BAR)	270(7.6)	445(12.6)	440(12.5)	520(14.7)	720(20.4)	850(24.1)	1,220(34.5)	1,925(54.5)	4,341(124)
300PSI(20.7BAR)			540(15.3)	660(18.7)	875(24.8)	1,080(30.6)	1,475(41.8)	2,475(70.1)	5,324(152.1)
350PSI(24.1BAR)			.	800(22.7)	995(28.2)	1,320(37.4)	1,665(47)	2,960(83.8)	6,340(181.1)
400PSI(27.6BAR)			.	.	1,130(32)	1,500(42.5)	.		.

In accordance with our policy of constant improvement of the products, we reserve the right to amend design, materials and specifications at any time without notice.