

The Stratex HYDRAULIC CASING PULLER

SLIPS & BOWLS

- Compact design
- Light weight
- Ready to be connected to your hydraulic pump
- Independent operation
- Vertical/horizontal operation



Hydraulic Casing Puller

Units		Metric Tons
CP 100	2 ⁵ / ₈ " - 4 ¹ / ₂ "	35 tons
CP 200	3 ¹ / ₂ " - 6 ⁵ / ₈ "	85 tons
CP 350	3 ¹ / ₂ " - 10 ³ / ₄ "	120 tons
CP 450	3 ¹ / ₂ " - 18"	250 tons

	Casing & Rod Slips	Bowl
	3 3 ¹ / ₂ 4" 5	3 - 5
	4" 5 6 7	4 ⁴ / ₁₆ - 8 ⁵ / ₈
	6 7 8 9	6 ⁵ / ₈ - 10 ³ / ₈
	10 - 18	12 ³ / ₄ - 18

The Stratex HYDRAULIC CASING PULLER

SLIPS & BOWLS



SIZE	CP100	CP200	CP350	CP450
MAX CASIN SIZE (B)	o4-1/2"	o7-5/8"	o12"	o18"
PULL IMP. TON	35,000	115,000	230,000	250,000
PSI (LB/IN ²)	2,500	3,000	3,000	3,600
NO. OF CYLINDER	2	2	2	2
CYLINDER BORE	3"	5"	7"	7"
PISTON ROD DIA	1-1/4"	2"	3"	3"
STROKE	18"	24"	25-3/8"	25-3/8"
DEPTH OF PULLER (C)	12"	16"	26"	28"
WIDTH OF PULLER (A)	18"	28"	42"	49"
HEIGHT EXTRACTED	32"	40"	48"	48"
HEIGHT EXTENDED	50"	64"	73-3/8"	73-3/8"
WEIGHT (LBS.)	188	500	1,400	NA

The Stratex **THREADED CASING, DRILL RODS** & CONNECTIONS



- LH/RH Thread
- Alloy steel threaded casing ends
- Flush joints
- API & custom-threaded specs available
- Casing sizes from 70mm
- Metric and Imperial Sizes available
- Drill rod sizes from 2

Overburden Drill Systems **ACCESSORIES**

- D.O.R. Drop-off reamer bits
- Drill pipe and subs
- Left threaded casings (left-hand HT allow ends)
- Casing drive shoes
- Stabilizers
- Hydraulic casing pullers
- Discharge heads
- Casing wing-nuts
- Shock subs
- Drill bits
- Fishing tools
- Air swivels



Manufactured under iso 9001 quality control